

LIVE TO PLAY LIVE®





M103 BLUE BOX

DESCRIPTION


- Fuzzes up your guitar signal, then duplicates it two octaves down
- Blend control sets mix of wet and dry signals

CONTROLS

- 1 OUTPUT controls overall volume of effect
- 2 BLEND controls mix or wet and dry signals
- 3 FOOTSWITCH toggles effect on/bypass (red LED indicates on)

POWER

The MXR Blue Box is powered by one 9-volt battery (remove bottom plate to install), a 9-volt AC adapter such as the Dunlop ECB003/ECB003E, or a DC Brick™ power supply.



DIRECTIONS

- Run a cable from your guitar to the Blue Box's INPUT jack and run another cable from the Blue Box's OUTPUT jack to your amplifier.
- Turn the OUTPUT knob clockwise to BOOST the effect's overall volume.

- Rotate the OUTPUT knob to increase overall volume of effect or counterclockwise to decrease it.
- Rotate BLEND knob clockwise to increase amount of sub-octave fuzz or counterclockwise to decrease it.

SAMPLE SETTINGS

7th ARMY FAT FUZZ		DROOLIN' IN THE RAIN		DEE PHUNK MAG-LITE	
OUTPUT	BLEND	OUTPUT	BLEND	OUTPUT	BLEND

SPECIFICATIONS

Input Impedance Output Impedance	1 MΩ <20 kΩ
Input Sensitivity Level	-56 dBV
Nominal Input Level	-22 dBV
Max Output Level	-5 dBV
Noise Floor*	>100 dBV
Bypass	Hardwire
Current Draw	
Effect On	4 mA
Effect Off	1.5 mA
Power Supply	9 volts DC

0 dBV = 1Vrms

*All controls @ full clock wise position. A-weighted

